

yuwell



CATALOG

HEMOCARE PRODUCTS

◦ BREATHCARE III (AUTO CPAP)

YH-680 (TOUCH SCREEN)

- Integrated Humidifier
 - Auto Ramp
 - Auto Heated Tube
- Auto Backlight
 - Smart Start/Stop
 - FPS-Tech
- Central Apnea Detection
 - Cloud Data Management
 - Wireless Transfer

Product Image	Information	YH-680
 G.W./N.W.: 3.7/2.4kg Packing: 1SET/CTN 41×31×24cm	Mode	CPAP、 Auto CPAP
	Pressure	4-20cmH2O
	Noise	27dBA±2dBA
	Efficient Humidifier	√
	FPS-Tech	√
	Auto-all	√
	Central Apnea Detection	√
	Leak Reminder	√
	Data Management	√
	Wireless Transfer	√

◦ BREATHCARE II (AUTO CPAP / BI-LEVEL)

YH-450

YH-830

- Smart Start/Stop
 - FPS-Tech
 - Central Apnea Detection
- High Pressure Reminder
 - Asphyxiation Reminder
 - Trigger Adjustment
- Cycle Adjustment
 - Slope Adjustment
 - Tidal Volume Adjustment

Product Image	Information	YH-450	YH-830
 G.W./N.W.: 3.6/2.4kg Packing: 1SET/CTN 40x27x17.5cm	Mode	CPAP、 Auto CPAP	CPAP、S、T、 ST、VGPS
	Pressure	4-20cmH2O	4-30cmH2O
	Noise	28dBA±2dBA	28dBA±2dBA
	Intergrated Humidifier	√	√
	Smart Humidification	√	√
	Cloud Data Management	√	√
	Wireless Transfer	√	√
	Leak Reminder	√	√
	Leak Compensation	√	√
	Altitude Adjustment	√	√

◦ BREATHCARE ECO (CPAP/AUTO CPAP)



YH-550

- FPS-Tech
- Leak Compensation
- Intergrated Humidifier
- Smart Start/Stop
- Cloud Data Management
- Central Apnea Detection
- Wireless Transfer
- Altitude Adjustment

◦ HIGH FLOW NASAL CANNULA OXYGEN THERAPY

HFNC HF-75A

- 7-inch touch screen
- Free of disinfection
- FiO2:21-100%
- FiO2 high/low alarm
- Tube blockage alarm
- Water level alarm
- Room temperature high/low alarm
- Oxygen source pressure High / Low alarm



◦ BREATHWEAR MASK SERIES



Fit



Convenience



Comfort



Light & Soft

- Rebound Silicone Cushion
- Adaptive Silicone Cushion
- Quiet Vent-Hole
- Quick-Release Connector
- Soft and Light Headgear



YN-01



YN-02



YN-03



YF-01



YF-03



YP-01

◦ OXYGEN CONCENTRATORS



SP-6

Portable oxygen concentrator

6L

6L large flow



Three power supply methods



Portable

- Integrated detachable adsorption tower
- Three power supply methods
- Intelligent alarm system
- Real-time respiratory rate detection and display
- High-precision breathing algorithm
- 2.8 inches LCD large screen display

◦ OXYGEN CONCENTRATORS



8F-5A



Medical
grade



Failure
detection



Castors

- Flow Range: 0.5 ~ 5L /min
- Sound Level: 48 dB(A)
- Oxygen Concentration: 95.5%-87%
- Minimum Operating Time: 30minutes



9F-5B



Medical
grade



Failure
detection



Castors

- Flow Range: 0.5 ~ 5L /min
- Sound Level: 42dB(A)
- Oxygen Concentration: 95.5%-87%
- Minimum Operating Time: 30minutes



7F-5B



Medical
grade



Failure
detection



Castors

- Flow Range: 0.5 ~ 5L /min
- Oxygen Concentration: 95.5%-87%
- Sound Level: ≤55dB(A)
- Minimum Operating Time: 30minutes



8F-10



Medical
grade



Failure
detection



Castors

- Flow Range: 1 ~ 10L /min
- Oxygen Concentration: 95.5%-87%
- Sound Level: 55dB(A)
- Minimum Operating Time: 30minutes

◦ SUCTION APPARATUS



7A-23A



Over-flow protection



Suction liner



Oil-free pump



Large jar



Castors

- Max Vacuum: $\geq 0.06\text{MPa}$
- Max Air Flow: $\geq 20\text{L/min}$
- Noise: $\leq 60\text{dBA}$
- Operating time: 30 minutes on, 30 minutes off

7A-23D



Over-flow protection



Oil-free pump



Foot switch



Large jar



Castors

- Power Voltage: AC220V , 50Hz
- Max negative pressure: $> 80\text{kPa}$
- Operation noise: $< 60\text{ dB (A)}$
- Max air flow: $30\pm 2\text{ L/min}$ (without jar); $26\pm 2\text{ L/min}$ (with jar)
- Liquid Collection Jar: 2500mL/pc , 2pieces

Product Image	Information	7A-23B	7A-23B Heavy Duty
A white, upright suction apparatus with two large, clear collection jars. It has a control panel at the top with a gauge and buttons. The unit is mounted on four small casters.	Input power	180VA	180VA
	Limit negative pressure	$> 80\text{kPa}$	$\geq 90\text{kPa}$
	Operation noise	$< 60\text{ dB (A)}$	$\leq 65\text{dB(A)}$
	Suction rate	$20\text{ L/min (with jar)}$	$40\text{ L/min (with jar)}$
	Liquid collection jar	2500mL/pc , 2pieces	
	Oil-free pump	✓	✓
	Over-flow protection	✓	✓
	Foot switch	✓	✓
	Large jar	✓	✓
	Castors	✓	✓

◦ PORTABLE PHLEGM SUCTION UNIT

7E-H1



Over-flow
protection



Suction
liner



Oil-free
pump

- Operation noise: $\leq 65\text{dB(A)}$ approximate 55db(A)
- Liquid Collection Jar: 1000mL, 1piece(PC material)
- Operating time: 30 minutes on, 30 minutes off

7E-G1



Over-flow
protection



Suction
liner



Oil-free
pump



lithium
battery



Wall-hung
shelf



Vehicle
use

- Operation noise: $\leq 65\text{dB}$ approximate 52db(A)
- Operating time: 30 minutes on, 30 minutes off
- Running time of battery operation: Approx. 60 minutes

7E-B5



High
pressure



Double
mute



Medical
grade

- Adjustable
- High efficiency
- Operation noise: approx. 50dB(A) (without vacuum)
- Liquid collection jar: 1000mL/pc
- Operating time: 30 minutes on, 30 minutes off

7E-A



Over-flow
protection



Oil-free
pump

- Operation noise: Noise: $\leq 60\text{dB(A)}$ approx. 50dB(A) (without vacuum)(CE)
- Liquid Collection Jar: 1000mL, 1piece
- Operating time: 30 minutes on, 30 minutes off

◦ NEBULIZER SERIES



M102

- Medical grade
- Nebulizer rate adjustable
- Small nebulizer particles
- Portable



M105

- Medical grade
- Nebulizer rate adjustable
- 2-grade regulating
- Small nebulizer particles
- Portable



403T

- Medical grade
- Nebulizer rate adjustable
- Oil-free pump
- Portable
- Small nebulizer particles



405B

- Medical grade
- Nebulizer rate adjustable
- Oil-free pump
- Small nebulizer particles
- Portable



407A

- Medical grade
- Nebulizer rate adjustable
- Oil-free pump
- Small nebulizer particles
- Portable



407C

- Medical grade
- Nebulizer rate adjustable
- Oil-free pump
- Non-stop operation
- Filter replacement prompt

◦ INFRARED THERMOMETER

YT-2



Fast
measurement



Vibration
guidance



Measuring
distance
guidance



Backlit
display

- Response time: 1 second
- Auto shut off: 30 seconds
- Measure distance: 0-5cm
- Memory retrieval: 10 memory groups

◦ ELECTRONIC BLOOD PRESSURE MONITOR

YE660E



Large Backlit display



Voice broadcast



Error action prompt

- 99 groups of memory
- Detection for cuff wearing
- Average of three measurements

YE660F



Large Backlit display



Voice broadcast



Error action prompt

- 90 groups of memory
- Detection for cuff wearing
- Average of three measurements

YE630CR



Voice broadcast



Bluetooth transmission



Lithium battery

- 50 groups of memory
- Detection for cuff wearing
- Prompt for movement
- All-in-one upper arm blood pressure monitor

◦ MEDICAL AUTOMATIC ELECTRONIC BLOOD PRESSURE MONITOR

YE990



Large Backlit display



Voice broadcast



Printing function

- Prompt for movement
- Supporting multiple transmission modes
- Animated voice prompt, for automatic measurement
- Pulse rate、Blood pressure level display



◦ ELECTRIC WHEELCHAIRS



D130AL

- Aluminum alloy frame
- Fixed arm rests and foot rests, foldable back
- Fold left and right
- 4 national patents



D130EL

- Aluminum alloy frame
- Fixed arm rests, adjustable foot rests
- Quick-release battery box
- Fold up and down
- 9 national patents



D210DL

- Iron frame
- Flip-up arm rests, adjustable foot rests, foldable back
- Strong power
- Fold left and right
- 4 national patents

Information	D130AL	D130EL	D210DL
Outdoor type	√	√	√
Manual and electric dual mode	√	√	√
Electromagnetic brake	√	√	√
Maximum speed	≤6km/h	≤6km/h	≤6km/h
Endurance mileage	≥20km	≥20km	≥20km
Motor power	130Wx2	130Wx2	210Wx2
Obstacle crossing height	≥40mm	≥40mm	≥40mm
Minimum turning radius	1.2m	1.2m	1.2m
Weight Capacity	≤100kg	≤100kg	≤100kg
Battery	Lithium battery DC 24Vx12 Ah	Lithium battery DC 24Vx12 Ah	Lithium battery DC 24Vx18Ah

◦ WHEELCHAIRS



K7

- Steel frame
- Detachable armrests
- Adjustable foot rests
- Fixed back
- Load: 227kg



2002

- Used for home rehabilitation, transportation, medical treatment, and outdoor activities for the injured, sick, and disabled
- Ultimate carrying capacity:182kg

◦ MATTRESSES WITH MECHANICAL PUMP



M5-C

- Head static
- CPR
- Transportable
- 5 inch
- Base cushion fixing strap
- All—around zipper



Striped

- Alternately simulate natural sleep rhythm, promote blood circulation and avoid local ischemia caused by long-term compression of tissues.

◦ OVERBED TABLE



YU616

- Environment-protection top
- Waterproof
- Easy to lift and lower
- Low noise
- Detachable
- G.W.: 10.5kg
- Size: 82.5×42×12.5cm

yuwell

Impact Distributors

HYDERABAD, INDIA - 500001

www.yuwell.co.in

f | t | in | @ | Yuwell Global

North India Distributor

Primark Global

A90 – Sector 69, Noida- 201301, U.P.

Sales@primarkglobal.com

Tel: 0120 4130203